

Guangdong, China

IEC60529:2013

YX-IPX8-30AC-100L

usd+20000-50000+pcs

wooden box package

ISO 20653:2013, DIN 40050-9:1993,

YueXin

1 pcs

T/T

30-45 days

100+pcs+30

30m IPX8 Diving Depth Test Machine , 100L Water Immersion Test Chamber

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

IP Grade:	IPX8
 Pressure Accuracy: 	1 KPa
• Test Scenario:	Environment Of Long Term Immersion Up To A Specified Pressure
 Depth Range: 	1-30m
Material:	304 Stainless Steel
 Opening Method: 	Cylinder Drive
• Power:	100w
Product Name:	Waterproof Immersion Soaking Test Chamber , Ipx8 Waterproof Test Equipment
• Highlight:	30m Water Immersion Test Chamber, 100L Water Immersion Test Chamber

Reliable 30m IPX8 Diving Depth Test Machine, 100L Immersion Test Chamber

Product introduction:

The specialty of this equipment lies in its cylinder-lifting can cover, which provides higher flexibility and adaptability for tests, making it suitable for a wider range of experimental needs. Meanwhile, the can cover can be quickly opened or closed to respond to emergencies or sudden situations, enhancing operational convenience and safety.

The device is equipped with a pressure sensor, which can display the internal pressure change synchronously.

- The tank cover is fastened with stainless steel can lid flange fasteners, and the seal is firm.
- Timing is performed by a time relay, and timing starts after the internal pressure reaches the set value.
- After the test is complete, the device automatically vents the pressure.

The tank cover is connected with a mechanical safety valve. If the set pressure exceeds the set pressure, the safety valve will release the pressure directly to ensure the safety of users.

The tank lid is lifted and lowered by cylinder driving to reduce operating pressure.

If the user needs to provide an external power supply for the sample, we can open a hole in the lid and provide a locking device (wire diameter <15mm)⁵.

Generl specifications:

Outer dimension	Approx W 610×D 780×H 1050 (mm)
Pressure accuracy	1 kPa
Power supply	220V/50Hz
Power	100w

The technical data:

ltem	Specification
Thickness of lid	15 mm
Flange thickness	20 mm
Tank thickness	3 mm
Equipment net weight	Approx 70 kg
pressure range	0-300 kPa
Water depth(maximum)	30 meters
Adjustment method	Automatic adjustment
Opening method	cylinder drive
Pressure accuracy	1 kPa
pressure error value	±2 kPa
Set pressure of safety valve	0.35 Mpa(350kPa)
Testing time ⁶	0-999 s/min/h
power supply	220V/50Hz
power	100 w

Remark:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multifunctional customized test solutions according to user requirements.

4 The formula of the corresponding relationship between pressure and water depth: P=9.8d (Unit :kPa,m).

5 Please wear insulating gloves during power-on test to avoid personal safety problems.

6 The time unit of the test can be freely selected, and it can be adjusted through the time relay before starting the test.

7 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 60L). If you need us to buy it on your behalf, you need to explain in advance.

8 The photos may not match the actual ones, and are for user reference only.

Product picture:



