

IPX1-IPX6K Waterproof Test Chamber Rugged Drip And Spray Testing Machine

Our Product Introduction

for more products please visit us on raintestchambers.com

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10
- Model Number: YX-IPX16KBSE-R400
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Product Name: IPX1-6 Waterproof Test Equipment , IP Grade Testing Machine
- Test Function: IPX1 IPX2 IPX3 IPX4 IPX5 IPX6 IPX4K IPX6K
- Diameter Of Detachable Turntable: 400mm
- Turntable Tilt: 0°or 15°(horizontal Direction)
- Operating Environment: Drip , Rain, Splash Water, Water Spray, Powerful Water Spray
- Turn Table Load Bearing: 40KG
- Rotating Speed: 1-5 Rounds Per Minute
- Controller: 7-inch Touch Screen + PLC
- Highlight: **IPX1 Waterproof Test Chamber, IPX6K Waterproof Test Chamber, Drip And Spray Testing Machine**

Product Description

Specific IPX1-6K Waterproof Test Chamber, Rugged Drip and Spray Testing Machine

General specifications:

Dimension	Outer : Approx W 1350×D 3700×H 1920 (mm); Inner : W 900×D 900×H 1050 (mm)
Material	External : steel plate; Internal : 304 stainless steel
Power supply	380V/50HZ
Power	4.0kw

Product overviews:

The product adopts internal spraying, with IPX4K/IPX6K ratings and a boosting function, enabling it to simulate and test the waterproof performance of equipment under severe conditions. Moreover, it is equipped with flow sensors and pressure sensors, which can accurately measure various data and improve the accuracy of testing.

For IPX5/6 testing, here are two spray modes: up and down sweeping water spray and fixed water spray⁵ (Spray water from back to front).

The flow rate is automatically adjusted by an electronic flow sensor, and the flow data will be displayed on the touch screen in real time⁶.

Use a pressure gauge to display the test water pressure.

The sample power socket (220V, 10A) is mounted on the right wall of the inner box, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁷.

There is a waterproof lighting inside, which is convenient for users to observe the test situation.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple language⁸.

Test time setting: 0-999min⁹.

Standard features for IPX1/2:

Item	Parameter
Drip area	600×600mm
Diameter of nozzles	0.4mm
Distance between nozzles	20mm
Water flow(IPX1) ¹⁰	0.36-0.54 L/min
Water flow(IPX2)	1.08-1.26L/min
Drip distance ¹¹	200mm

Standard features for IPX3/4K:

Item	Parameter
Radius of swivel tube ¹²	R400
Diameter of swivel tube	800mm
Internal diameter of swivel tube	15mm
Internal diameter of nozzle	IPX3/4 : 0.4mm; IPX4K : 0.8mm
Number of nozzles of swivel tube	See remark ¹³
Distance between nozzles	50mm
Speed of rotation of the swivel tube	60 degree/s
Swing pipe angle	IPX3 : 120°; IPX4/IPX4K : 350°
Water volume flow	IPX3(L/min) : 1.1 ; IPX4(L/min) : 1.8 ; IPX4K(L/min):15.0
Flow error range	±5%

Standard features for IPX5/6K:

Item	Parameter
Diameter of nozzles	IPX5,IPX6K : 6.3mm; IPX6 :12.5mm
Water flow	IPX5 : 12.5±0.625 L/min IPX6 : 100.0±5.0L/min IPX6K : 75.0±3.75L/min
Spray distance ¹⁴	2.7m
Spray direction	Spray from back to front
Spray height ¹⁵	800mm
Nozzle swing speed	0-20 cycle/min

Remark:

- 1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.
- 2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.
- 3 Standard load-bearing upper limit of turntable is 50kg, but also can be customized per requirements. Turntables of $\phi 200\text{mm}$ are provided for replacement.
- 4 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.
- 5 If the sample height exceeds 150mm, it is recommended to choose the swing spray method.
- 6 Use flow sensor to adjust water flow automatically, the flow is set according to the corresponding test options, and does not support custom settings.
- 7 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.
- 8 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.
- 9 It is recommended to set the test time according to the test standard. The water temperature will rise due to long time test which has an impact on the test results.
- 10 The data is calculated based on the dripping area, $\text{IPX1: } 0.6 \times 0.6 \times (0.001 - 0.0015) = 0.00036 - 0.00054 \text{m}^3/\text{min}$ (that is 0.36-0.54L/min).
- 11 200mm is the distance from the nozzle to the sample specified in the standard, and the user needs to adjust the height of the turntable to meet the distance requirement.
- 12 Multiple specifications of pendulum tubes can be provided, please confirm clearly before placing an order; if other specifications are added after purchase, the equipment needs to be returned to the factory to replace hardware and programs.
- 13 The specifications of swing pipe for IPX3/4 rain test, as shown in the figure below:

**Table 9 – Total water flow rate q_v under IPX3 and IPX4 test conditions –
Mean flow rate per hole $q_{v1} = 0.07 \text{ l/min}$**

Tube radius R mm	Degree IPX3		Degree IPX4	
	Number of open holes $N^{1)}$	Total water flow q_v l/min	Number of open holes $N^{1)}$	Total water flow q_v l/min
200	8	0.56	12	0.84
400	16	1.1	25	1.8
600	25	1.8	37	2.6
800	33	2.3	50	3.5
1 000	41	2.9	62	4.3
1 200	50	3.5	75	5.3
1 400	58	4.1	87	6.1
1 600	67	4.7	100	7.0

¹⁾ Depending on the actual arrangement of the hole centres at the specified distance, the number of open holes N may be increased by 1.

- 14 This distance is the range from the nozzle to the center of the turntable. If the user wants to extend the spraying distance, he needs to explain in advance.
- 15 Since the IPX5 water spray is in a parabolic shape, the water spray range will be lower than this height, and the measured maximum water spray height is close to 550mm.
- 16 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 40L). If you need us to buy it on your behalf, you need to explain in advance.
- 17 The photos may not match the actual ones, and are for user reference only.

Detail picture:



Tags: Waterproof Testing Equipment , IP Grade Climatic Chamber , IPX1-6K Environmental Machine



Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China