

Comprehensive Waterproof Test Equipment IPX1 IPX2 IPX3 IPX4 IPX5 IPX6 IPX4K IPX6K

Our Product Introduction

for more products please visit us on raintestchambers.com

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10
- Model Number: YX-IPX16GSE-R400
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Product Name: Waterproof Test Equipment
- Service Environment: Drip、 Rain、 Splash Water、 Water Spray、 Powerful Water Spray
- Window Material: Tempered Glass
- Turntable Tilt: 0°or 15°(horizontal Direction)
- Test Function: IPX1 IPX2 IPX3 IPX4 IPX5 IPX6
- Turn Table Load Bearing: 40KG
- Rotating Speed: 1-5 Rounds Per Minute
- Controller: 7-inch Touch Screen + PLC
- Highlight: **Comprehensive Waterproof Test Equipment, Waterproof Test Equipment IPX1, Waterproof Test Equipment IPX2**



Product Description

IPX1-6K Rain Testing Chamber, Comprehensive Waterproof Test Equipment

General specifications:

Dimension	Outer : Approx W 3900×D 1090×H 1760 (mm); Inner : W 900×D 900×H 1050 (mm)
Material	External : steel plate; Internal : 304 stainless steel
Power supply	380V/50HZ
Power	3.0kW

Product presentation:

Compared with the conventional water spray test chamber, the particularity of this equipment lies in its side-spraying direction, that is, it sprays the specific area on the surface of the equipment from left to right. This spraying method can accurately cover the target area to ensure the comprehensiveness of the test.

- A protective cover is installed at the bottom of the drip tank to prevent the head from being hurt by the nozzle during operation.
- The equipment uses a high-quality servo motor to drive the swing tube, so that the swing angle is more precise and the noise is low.
- For IPX5/6 testing, here are two spray modes: up and down sweeping water spray and fixed water spray⁵ (spray water from left to right).
- There is a water storage tank inside the equipment and a water level control system. When the water is full, it will prompt, and when it is short of water, it will alarm.
- The flow rate is automatically adjusted by an electronic flow sensor, and the flow data will be displayed on the touch screen in real time⁶.
- Use a pressure gauge to display the test water pressure.
- The sample power socket (220V, 10A) is mounted on the right wall of the inner box, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁷.
- There is a waterproof lighting inside, which is convenient for users to observe the test situation.
- Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁸.
- Test time setting: 0-999min⁹.
- Protection measures: short circuit protection, water shortage alert.
- Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Technical data for IPX1/2:

Item	Parameter
Drip area	600×600mm
Diameter of nozzles	0.4mm
Distance between nozzles	20mm
Water flow(IPX1) ¹⁰	0.36-0.54 L/min
Water flow (IPX2)	1.08-1.26L/min
Drip distance ¹¹	200mm

Technical data for IPX3/4:

Item	Parameter
Radius of swivel tube ¹²	R400
Diameter of swivel tube	800mm
Internal diameter of swivel tube	15mm
Internal diameter of nozzle	0.4mm
Number of nozzles of swivel tube	See remark ¹³
Distance between nozzles	50mm
Speed of rotation of the swivel tube	60 degree/s
Swing pipe angle	IPX3 : 120°; IPX4 : 350°
Water volume flow	IPX3(L/min) : 1.1 ; IPX4(L/min) : 1.8
Flow error range	±5%

Technical data for IPX5/6:

Item	Parameter
Diameter of nozzles	IPX5 : 6.3mm; IPX6 : 12.5mm
Water flow	IPX5 : 12.5±0.625 L/min IPX6 : 100.0±5.0L/min
Spray distance ¹⁴	2.7m
Spray direction	Spray from left to right
Spray height ¹⁵	800mm
Nozzle swing speed	0-20 cycle/min

Remark:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model

and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 Standard load-bearing upper limit of turntable is 50kg, but also can be customized per requirements. Turntables of $\phi 200\text{mm}$ are provided for replacement.

5 If the sample height exceeds 150mm, it is recommended to choose the swing spray method.

6 Use flow sensor to adjust water flow automatically, the flow is set according to the corresponding test options, and does not support custom settings.

7 Please inform in advance if the voltage (220V) does not match the actual needs so that we can provide customized solutions for you.

8 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

9 It is recommended to set the test time according to the test standard. The water temperature will rise due to long time test which has an impact on the test results.

10 The data is calculated based on the dripping area, $\text{IPX1}: 0.6 \times 0.6 \times (0.001 - 0.0015) = 0.00036 - 0.00054 \text{m}^3/\text{min}$ (that is 0.36-0.54L/min).

11 200mm is the distance from the nozzle to the sample specified in the standard, and the user needs to adjust the height of the turntable to meet the distance requirement.

12 Multiple specifications of pendulum tubes can be provided, please confirm clearly before placing an order; if other specifications are added after purchase, the equipment needs to be returned to the factory to replace hardware and programs.

13 The specifications of swing pipe for IPX3/4 rain test, as shown in the figure below:

Table 9 – Total water flow rate q_v under IPX3 and IPX4 test conditions –
Mean flow rate per hole $q_{v1} = 0,07 \text{ l/min}$

Tube radius R mm	Degree IPX3		Degree IPX4	
	Number of open holes $N^{1)}$	Total water flow q_v l/min	Number of open holes $N^{1)}$	Total water flow q_v l/min
200	8	0,56	12	0,84
400	16	1,1	25	1,8
600	25	1,8	37	2,6
800	33	2,3	50	3,5
1 000	41	2,9	62	4,3
1 200	50	3,5	75	5,3
1 400	58	4,1	87	6,1
1 600	67	4,7	100	7,0

1) Depending on the actual arrangement of the hole centres at the specified distance, the number of open holes N may be increased by 1.


14 This distance is the range from the nozzle to the center of the turntable. If the user wants to extend the spraying distance, he needs to explain in advance.

15 Since the IPX5 water spray is in a parabolic shape, the water spray range will be lower than this height, and the measured maximum water spray height is close to 550mm.

16 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 40L). If you need us to buy it on your behalf, you need to explain in advance.

17 The photos may not match the actual ones, and are for user reference only.

Product detail image:



servo motor

Tags: IP Waterproof Test Equipment , Drip and Water Jet Test Chamber , IP Grade Testing Machine



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China