

220V 50HZ Rain Test Machine , Accurate 1800mm Drip Test Equipment

Our Product Introduction

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013 , DIN 40050-9:1993 , IEC60529:2013 VW80000:2017 LV124 K-10
- Model Number: YX-IPX12A-1800
- Minimum Order Quantity: 1pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Product Name: Environmental Testing Equipment, Humidity Temperature Test Chamber
- Drip Area: 1800×1800mm
- Distance Between Nozzles: 20mm
- Turn Table Load Bearing: 50KG
- Drip Distance: 200mm
- Turntable Tilt: 0° Or 15°
- IP Grade: IPX12
- Turn Table Diameter: 1000mm
- Highlight: **220V Rain Test Machine,
50HZ Rain Test Machine,
1800mm Drip Test Equipment**

for more products please visit us on raintestchambers.com

Product Description

IPX1 IPX2 load-bearing Rain Test Machine , Accurate 1800 mm Rain Test Device

General specifications:

Dimension	Outside: Approx W 1800×D 1800×H 2700 (mm); Inside: Approx W 200×H 350 (mm)
Material	Outer: Formed Aluminum; Inner: 304 stainless steel

Product introduction:

Highlighting its primary strengths, this drip rain tester possesses a strong frame structure that promotes ease of movement and ensures a trouble-free operation during testing sessions. Moreover, the column-shaped design introduces a wide range of height adjustments for the drip plate, fulfilling the testing requirements of samples of different sizes.

The drip board is made of stainless steel, with 0.4mm needle nozzles evenly distributed(the water level is invisible).

The drip board can be lifted and lowered by chain drive + screw combination device, and has a photoelectric detection switch, which can stop falling at a distance of 200mm from the sample.

A protective cover is installed under the drip board to protect personnel from being hurt by the nozzle.

The sample power socket (220V, 10A) is mounted on the side of the turntable, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁵.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁶.

Floor-standing structure: the bottom can be fixed to the ground with expansion screws to make the equipment firm and stable.

Protection measures: short circuit protection, safety shield protection.

Four pillars are used to support the drip board, which is stable and firm.

The top is lifted and lowered by an electric hoist, with a load capacity of 200kg > the weight of the water tank when fully loaded (approx. 100kg).

There are reinforcement bars welded inside the drip plate to effectively prevent bursting due to high water pressure.

Needle nozzles are made of replaceable plastic nozzles, easy to maintain and delivered with needle nozzles.

There are mobile casters and foot brakes at the bottom, which can be moved and fixed as a whole.

The installation of the drip test equipment is very simple, only need to fix the right side of the chassis on top of the frame, through the locking screws.

The main technical parameters :

Item	Specification
Drip area	1800×1800mm
Diameter of nozzles	0.4mm
Distance between nozzles	20mm
Test time	0-999min
Drip board height	800-1800mm
Flow control ⁷	Manual adjustment with flow meter
Flow meter range	0-10.0 L
Water flow(IPX1) ⁸	2.56-3.84L/min
Water flow(IPX2)	7.68-8.96L/min
Drip distance ⁹	200mm
Power supply	220V/50HZ
Power	1.5kW

Application:

We specialize in a broad range of rain testers, catering to a diverse array of industries, spanning from plastics and rubbers to pharmaceuticals, cosmetics, and everything between, including paints, coatings, printing inks, paper products, food industry, textiles, automotive components, packaging solutions, construction materials, and electrical/electronics. Our instruments are pivotal in delivering essential test data, fueling scientific research, product innovation, and quality control measures.

Notices:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 Standard load-bearing upper limit of turntable is 50kg, but also can be customized per requirements.

5 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

6 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

7 The standard model is adjusted by a flowmeter, and the upper surface of the float is aligned with the scale to read the data; if you need to export the test data, you can choose a flow sensor.

8 The data is calculated based on the dripping area, $IPX1: 1.6 \times 1.6 \times (0.001 - 0.0015) = 0.00256 - 0.00384 m^3/min$ (that is 2.56-3.84L/min). When reading the flowmeter, the second digit after the decimal point is the estimated reading data, not accurate data; if the user is concerned about the accuracy of the data, a flow sensor can be selected through negotiation.

Second characteristic numeral	Test means	Water flow rate	Duration of test	Test conditions, see
0	No test required	—	—	—
1	Drip box Figure 3 Enclosure on turntable	$1^{+0.5}_{-0}$ mm/min	10 min	14.2.1
2	Drip box Figure 3 Enclosure in 4 fixed positions of 15° tilt	$3^{+0.5}_{-0}$ mm/min	2.5 min for each position of tilt	14.2.2

9 200mm is the distance from the nozzle to the sample specified in the standard, and the user needs to adjust the height of the drip board to meet the distance requirement.

10 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 40L). If you need us to buy it on your behalf, you need to explain in advance.

11 The photos may not match the actual ones, and are for user reference only.

Detail photo:



caster

Tags: Dripping Rain Testing Machine, Water Drip Test Equipment, Dripping Climatic Chamber



Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China