

IPX1-2 Drip Test Equipment , 2400mm Rain Tester For Heavy Weights

Our Product Introduction

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013 , DIN 40050-9:1993 , IEC60529:2013 VW80000:2017 LV124 K-10
- Model Number: YX-IPX12A-2400
- Minimum Order Quantity: 1pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Product Name: Environmental Testing Equipment, Humidity Temperature Test Chamber
- Drip Area: 2400×2400mm
- Distance Between Nozzles: 20mm
- Drip Distance: 200mm
- IP Grade: IPX12
- Turn Table Diameter: 600mm
- Turn Table Load Bearing: 30KG
- Turntable Tilt: 0° Or 15°
- Highlight: **IPX1-2 Drip Test Equipment, 2400mm Rain Tester, Heavy Weights Rain Tester**

for more products please visit us on raintestchambers.com

Product Description

IPX1-2 Drip Test Equipment , 2400 mm Rain Tester for Heavy Weights

General specifications:

Dimension	Approx W 1320×D 1020×H 2420 (mm)
Material	Formed Aluminum

Product introduction:

The main features of this water drip test machine are its sturdy frame that allows for easy mobility and smooth operation during testing. The column-style design enables a wide range of height adjustment for the drip plate, making it suitable for testing samples of various sizes.

The drip board is made of stainless steel, with 0.4mm needle nozzles evenly distributed (the water level is invisible). And it can be lifted and lowered by the electric hoist device, and has a photoelectric detection switch, which can stop falling at a distance of 200mm from the sample. Also, a protective cover is installed under the drip board to protect personnel from being hurt by the nozzle.

The sample power socket (220V, 10A) is mounted on the side of the turntable, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁵.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁶.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Protection measures: short circuit protection, safety shield protection.

Drip board lifting has high and low level limitations, using two metal sensors to sense.

Four pillars are used to support the drip board, which is stable and firm.

The water inlet of the drip tray comes in from the centre of the top and spreads out in all directions so that the water drips relatively evenly.

There are mobile casters and foot brakes at the bottom, which can be moved and fixed as a whole.

The installation of the drip test equipment is very simple, only need to fix the right side of the chassis on top of the frame, through the locking screws.

The main technical parameters :

Item	Specification
Drip area	2400×2400mm
Diameter of nozzles	0.4mm
Distance between nozzles	20mm
Test time	0-999min
Drip board height	800-1800mm
Flow control ⁷	Manual adjustment with flow meter
Flow meter range	0-4.0 L
Water flow(IPX1) ⁸	0.64-0.96L/min
Water flow(IPX2)	1.92-2.24L/min
Drip distance ⁹	200mm
Power supply	220V/50HZ
Power	1.0kW

Operating environment:

Our expertise lies in providing a diverse range of rain testers tailored to various industries, encompassing plastics, rubbers, paints, coatings, printing inks, paper products, pharmaceuticals, food processing, cosmetics, textiles, automotive components, packaging solutions, construction materials, as well as electrical and electronic devices. These testers are pivotal in furnishing vital test data, essential for advancing scientific research, fostering product innovation, and ensuring rigorous quality control measures.

Announcements:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 Standard load-bearing upper limit of turntable is 30kg, but also can be customized per requirements.

4 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

5 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

6 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

7 The standard model is adjusted by a flowmeter, and the upper surface of the float is aligned with the scale to read the data; if you need to export the test data, you can choose a flow sensor.

8 The data is calculated based on the dripping area, $IPX1: 0.8 \times 0.8 \times (0.001 \sim 0.0015) = 0.00064 \sim 0.00096 \text{ m}^3/\text{min}$ (that is $0.64 \sim 0.96 \text{ L/min}$). When reading the flowmeter, the second digit after the decimal point is the estimated reading data, not accurate data; if the user is concerned about the accuracy of the data, a flow sensor can be selected through negotiation.

9 200mm is the distance from the nozzle to the sample specified in the standard, and the user needs to adjust the height of the drip board to meet the distance requirement.

10 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 40L). If you need us to buy it on your behalf, you need to explain in advance.

11 The photos may not match the actual ones, and are for user reference only.

Second characteristic numeral	Test means	Water flow rate	Duration of test	Test conditions, see
0	No test required	—	—	—
1	Drip box Figure 3 Enclosure on turntable	$1^{+0.5}_0$ mm/min	10 min	14.2.1
2	Drip box Figure 3 Enclosure in 4 fixed positions of 15° tilt	$3^{+0.5}_0$ mm/min	2.5 min for each position of tilt	14.2.2

Detail picture:



lifting support

Tags: Vertical Drip Test Equipment, IPX1-2 Dripping Rain Test Machine, Dripping Climatic Chamber

YUEXIN® Guangzhou Yuexin Test Equipment Co., Ltd.

☎ 18122303372 ✉ mft@yxipx.com 🌐 raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China