



600mm Rain Test Chamber, IPX1 IPX2 Waterproof Test Equipment With Flow Sensor

Our Product Introduction

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013 , DIN 40050-9:1993 , IEC60529:2013 VW80000:2017 LV124 K-10
- Model Number: YX-IPX12BE-600
- Minimum Order Quantity: 1pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Drip Area: 600×600mm
- Distance Between Nozzles: 20mm
- Drip Distance: 200mm
- IP Grade: IPX12
- Turn Table Diameter: 600mm
- Turn Table Load Bearing: 30KG
- Turntable Tilt: 0° Or 15°
- Product Name: Environmental Testing Equipment, Humidity Temperature Test Chamber
- Highlight: **600mm Rain Test Chamber, Rain Test Chamber IPX1, IPX2 Waterproof Testing Equipment**

for more products please visit us on raintestchambers.com

Product Description

600 mm Rain Test Chamber for IPX1 IPX2, Waterproof Tester with Flow Sensor

General specifications:

Dimension	External: Approx W 1250×D 1020×H 1750 (mm) Internal: W 800×D 800×H 1000 (mm)
Material	Outward: steel plate Within: 304 stainless steel

Applicable environment:

We specializing in rain testers caters to a multitude of fields, spanning plastics, rubbers, paints & coatings, printing inks, paper goods, pharmaceuticals, food processing, cosmetics, textiles, auto parts, packaging solutions, construction materials, and electrical/electronic items. It plays a crucial role in supplying essential test data that informs scientific research, product innovation, and quality control processes.

Product description:

Distinct from the stand and wall-mounted models, this box-shaped rain test enclosure boasts mobility, promotes water conservation through recycling for experiments, aligns with eco-friendly principles, and serves as a versatile tool for waterproof testing of compact devices.

The drip tank is made of stainless steel, with 0.4mm needle nozzles evenly distributed, and the water level is invisible. There is a water storage tank inside the equipment and a water level control system. When the water is full, it will prompt, and when it is short of water, it will alarm.

The sample power socket (220V, 10A) is mounted on the right wall of the inner box, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁵.

There is a waterproof lighting inside, which is convenient for users to observe the test situation.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁶.

Test time setting: 0-999min⁷.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Protection measures: short circuit protection, water shortage alert.

The standard version uses a glass flow meter to regulate the flow rate, and can be upgraded to use a sensor to regulate the flow rate, and the data is displayed on the touch screen.

The water storage tank is placed in front of the inner tank, which is convenient for cleaning and maintenance.

Blue and white colours are used in the shell, which is in line with the theme of waterproof test.

Drip plate is fixed, by lifting the height of the turntable to achieve the adjustment of the drip distance, turntable lifting range 0-500mm.

Four universal load-bearing casters at the bottom, easy to move.

The main technical parameters :

Item	Specification
Drip area	600×600mm
Distance between nozzles	20mm
Diameter of nozzles	0.4mm
Flow control ⁸	Manual adjustment with flow meter
Water flow(IPX1) ⁹	0.36-0.54 L/min
Water flow(IPX2)	1.08-1.26 L/min
Flow meter range	0-2.0 L
Drip distance ¹⁰	200mm
Power supply	220V/50HZ
Power	1.0kW

Notes:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

3 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

4 Standard load-bearing upper limit of turntable is 30kg, but also can be customized per requirements.

5 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

6 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

7 It is recommended to set the test time according to the test standard. The water temperature will rise due to long time test which has an impact on the test results.

8 The standard model is adjusted by a flowmeter, and the upper surface of the float is aligned with the scale to read the data; if you need to export the test data, you can choose a flow sensor.

9 The data is calculated based on the dripping area, $IPX1: 0.6 \times 0.6 \times (0.001 - 0.0015) = 0.00036 - 0.00054 m^3/min$ (that is 0.36-0.54L/min). When reading the flowmeter, the second digit after the decimal point is the estimated reading data, not accurate data; if the user is concerned about the accuracy of the data, a flow sensor can be selected through negotiation.

Second characteristic numeral	Test means	Water flow rate	Duration of test	Test conditions, see
0	No test required	—	—	—
1	Drip box Figure 3 Enclosure on turntable	$1^{+0.5}_{-0}$ mm/min	10 min	14.2.1
2	Drip box Figure 3 Enclosure in 4 fixed positions of 15° tilt	$3^{+0.5}_{-0}$ mm/min	2.5 min for each position of tilt	14.2.2

10 200mm is the distance from the nozzle to the sample specified in the standard, and the user needs to adjust the height of the turntable to meet the distance requirement.

11 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 40L). If you need us to buy it on your behalf, you need to explain in advance.

12 The photos may not match the actual ones, and are for user reference only.

Detail photo:



power

Tags: Dripping Testing Machine, Water Drip Test Chamber, IPX1 IPX2 Rain Test Chamber

YUEXIN® Guangzhou Yuexin Test Equipment Co., Ltd.

18122303372 mft@yxipx.com raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China