

Durable IPX3 IPX4 R600 mm Swing Nozzle Rainfall Test Machine with Flow Sensor

Our Product Introduction

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10
- Model Number: YX-IPX34CE-R600
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- IP Code: IPX3 IPX4
- Turn Table Load Bearing: 30KG
- Rotating Speed: 1-5 Rounds Per Minute
- Turn Table Diameter: 400mm
- Radius Of Swivel Tube: R600mm - R1600mm
- Type: Rain Spray Environmental Equipment
- Experimental Scenarios: Rain、 Splash Water
- Commodity Name: Swing Pipe Rain Test Apparatus , Waterproof Testing Machine
- Highlight: **ipx3 water spray test equipment , ipx4 water spray test equipment , ipx4 ipx3-4 rain spray test equipment**

for more products please visit us on raintestchambers.com

Product Description

Durable IPX3 IPX4 R600 mm Swing Nozzle Rainfall Test Machine with Flow Sensor

General specifications:

Outer Dimension	L1200*W600*H1200
Material	304 stainless steel
Power supply	220V/50HZ
Power	1.0kW

Description of Rain Spray Test Machine:

This model of rain test equipment employs flow sensors for monitoring fluid flow, enabling high-precision measurements with exceptional reliability and stability.

The counterweight is added at the bottom of the case to lower the center of gravity of the case and make the device more stable when swinging.

There is a water storage tank inside the equipment and a water level control system. When it is short of water, it will alarm.

The sample power socket (220V, 10A) is mounted under the control cabinet, which is convenient for the user to do the live test of the sample;

and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding ⁵.

The swing tube is driven by a servo motor, with precise swing angle and low noise.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁶.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Protection measures: short circuit protection, water shortage alert.

All 304 stainless steel body, excellent material, will not rust.

Both sides of the column adopts a slightly inclined design, when splash test, the water sprayed on the cabinet will flow out from the inside, will not bring into contact with the electric control part, to protect the electrical safety of the equipment.

Pendulum using CNC technology processing, nozzle spacing of 50mm, stainless steel, factory will be high-pressure rinsing, to avoid clogging of impurities.

The swing angle can be customised, such as swinging from the bottom to the top to simulate the splashing situation.

The diameter of the rotary table is matched according to the specifications of the pendulum tube, such as R200-φ200mm rotary table, R400-φ400mm rotary table.

Technical parameters :

Item	Specification
Radius of swivel tube ⁷	R600
Diameter of swivel tube	1200mm
Internal diameter of swivel tube	15mm
Internal diameter of nozzle	0.4mm
Number of nozzles of swivel tube	See remark ⁸
Distance between nozzles	50mm
Test time	0-999min
Speed of rotation of the swivel tube	60 degree/s
Swing pipe angle	IPX3:120°; IPX4:350°
Water volume flow	IPX3: 1.8(L/min) ; IPX4: 2.6(L/min)
Water pressure	Not adjustable (pressure gauge display)
Power supply	220V/50HZ
Power	1.0kW

Usage setting:

The adaptable Swing Nozzle Rain Test Machine excels in simulating rainfall scenarios for extensive products, facilitating rigorous assessments of water-resistance, sealing durability, and longevity in automotive components, outdoor electronics, construction materials, and a vast array of additional items. Its diverse range of models addresses the unique requirements across various testing environments.

Remark:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 Standard load-bearing upper limit of turntable is 30kg, but also can be customized per requirements.

5 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

6 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

7 The swing pipe can be equipped with a variety of specifications, which can be selected according to the sample size range (satisfying the spray distance <200mm), please confirm clearly before placing an order.

8 The specifications of swing pipe for IPX3/4 rain test, as shown in the figure below:

**Table 9 – Total water flow rate q_v under IPX3 and IPX4 test conditions –
Mean flow rate per hole $q_{v1} = 0,07$ l/min**

Tube radius R mm	Degree IPX3		Degree IPX4	
	Number of open holes $N^{1)}$	Total water flow q_v l/min	Number of open holes $N^{1)}$	Total water flow q_v l/min
200	8	0,56	12	0,84
400	16	1,1	25	1,8
600	25	1,8	37	2,6
800	33	2,3	50	3,5
1 000	41	2,9	62	4,3
1 200	50	3,5	75	5,3
1 400	58	4,1	87	6,1
1 600	67	4,7	100	7,0

1) Depending on the actual arrangement of the hole centres at the specified distance, the number of open holes N may be increased by 1.

9 The photos may not match the actual ones, and are for user reference only.

Detail photo:



swing pipe

Tags: Rain Spray Testing Machine, Rain Test Equipment, IPX3 IPX4 Waterproof Machine



Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China