

Suitable IPX3-4 R800 mm Oscillating Tube Rain Test Machine with Flow Sensor

Our Product Introduction

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10
- Model Number: YX-IPX34CE-R800
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- IP Code: IPX3 IPX4
- Turn Table Diameter: 600mm
- Turn Table Load Bearing: 40KG
- Experimental Scenarios: Rain、 Splash Water
- Rotating Speed: 1-5 Rounds Per Minute
- Type: Rain Spray Environmental Equipment
- Radius Of Swivel Tube: R600mm - R1600mm
- Commodity Title: Swing Pipe Rain Test Apparatus , Waterproof Test Equipment
- Highlight: **ipx3 rain test machine, ipx3 rain testing machine, ipx4 rain test machine**

for more products please visit us on raintestchambers.com

Product Description

Suitable IPX3-4 R800 mm Oscillating Tube Rain Test Machine with Flow Sensor

General specifications:

Outer Size	L1600*W600*H1400
Material	304 stainless steel
Power supply	220V/50HZ
Power	1.0kW

The main information of IPX3 IPX4 rain test machine:

The rain spray test apparatus utilizes advanced flow sensors to keep track of fluid movement, ensuring meticulous measurements of unparalleled reliability and steadfast stability.

The counterweight is added at the bottom of the case to lower the center of gravity of the case and make the device more stable when swinging.

There is a water storage tank inside the equipment and a water level control system. When it is short of water, it will alarm.

The sample power socket (220V, 10A) is mounted under the control cabinet, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁵. The swing tube is driven by a servo motor, with precise swing angle and low noise.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁶.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Protection measures: short circuit protection, water shortage alert.

The swing angle of the pendulum tube can be customised to meet more scenarios of testing needs.

The cabinet has been weighted, which can effectively reduce the centre of gravity and make the pendulum swing more smoothly without great shaking.

Pendulum using CNC technology processing, nozzle spacing of 50mm, stainless steel, factory will be high-pressure rinsing, to avoid clogging of impurities.

The swing angle can be customised, such as swinging from the bottom to the top to simulate the splashing situation.

Flow rate, swing angle, etc. have been internally calibrated and measured by a third party before shipment to comply with standards such as IEC60529 and EN60598.

Spray water can not be recycled, the test need to maintain a continuous water inlet, the internal water tank, if due to accidental water cut off, it will not affect the progress of the test, you can continue to spray water.

Standard parameters :

Item	parameters
Radius of swivel tube ⁷	R800
Diameter of swivel tube	1600mm
Internal diameter of swivel tube	15mm
Internal diameter of nozzle	0.4mm
Number of nozzles of swivel tube	See remark ⁸
Distance between nozzles	50mm
Test time	0-999min
Speed of rotation of the swivel tube	60 degree/s
Swing pipe angle	IPX3:120°; IPX4:350°
Water volume flow	IPX3: 2.3(L/min) ; IPX4: 3.5(L/min)
Water pressure	Not adjustable (pressure gauge display)
Power supply	220V/50HZ
Power	1.0kW

Working setting:

Designed for versatility, the Swing Nozzle Rain Test Machine specializes in mirroring realistic rain patterns for larger-scale products, allowing for meticulous examinations of waterproof capabilities, sealing robustness, and resilience of automotive parts, exterior electronic devices, architectural materials, and numerous other products. Its customizable models fulfill the specific demands of different testing applications.

Cautions:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 Standard load-bearing upper limit of turntable is 40kg, but also can be customized per requirements.

5 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

6 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

7 The swing pipe can be equipped with a variety of specifications, which can be selected according to the sample size range (satisfying the spray distance <200mm), please confirm clearly before placing an order.

8 The specifications of swing pipe for IPX3/4 rain test, as shown in the figure below:

**Table 9 – Total water flow rate q_v under IPX3 and IPX4 test conditions –
Mean flow rate per hole $q_{v1} = 0,07$ l/min**

Tube radius R mm	Degree IPX3		Degree IPX4	
	Number of open holes $N^{1)}$	Total water flow q_v l/min	Number of open holes $N^{1)}$	Total water flow q_v l/min
200	8	0,56	12	0,84
400	16	1,1	25	1,8
600	25	1,8	37	2,6
800	33	2,3	50	3,5
1 000	41	2,9	62	4,3
1 200	50	3,5	75	5,3
1 400	58	4,1	87	6,1
1 600	67	4,7	100	7,0

¹⁾ Depending on the actual arrangement of the hole centres at the specified distance, the number of open holes N may be increased by 1.

9 The photos may not match the actual ones, and are for user reference only.

Detail image:



filter

Tags: Rain Spray Climatic Apparatus for IPX3 IPX4, Rain Spray Testing Machine, IPX3 IPX4 Waterproof Device

YUEXIN® Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China