

Guangdong, China

usd+20000-50000+pcs wooden box package

YX-IPX56AM

1 pcs

T/T

ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10

# IPX5 IPX6 Touch Control Water Jet Tester Spray Up, Down, Left and Right

# **Basic Information**

- Place of Origin:
- Brand Name: YueXin
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time: 30-45 days
- Payment Terms:
- Supply Ability:



# **Product Specification**

- IP Grade:
- IPX5 IPX6 • Turn Table Load Bearing:
- Turn Table Diameter:
- Application Scenarios:
- Rotating Speed:
- Controller:

500KG

100+pcs+30

- Turntable Height: 600mm (non-lifting)

- Highlight:

- 1000mm
- Water Spray, Powerful Water Spray
  - 0-5 Rounds Per Minute
- Part Name:

- - - 7-inch Touch Screen + PLC
      - IPX5 IPX6 Water Jet Test Device , Water Jet Environmental Test Machine
        - ipx5 water jet testing machine, ipx6 water jet testing machine, ipx6 ipx5-6 water jet test machine

Our Product Introduction

# IPX5 IPX6 Touch Control Water Jet Tester Spray Up, Down, Left and Right

#### Generl specifications:

Outside dimension	Approx W 1100×D 900×H 1300 (mm)
Material	304 stainless steel
Power supply	380V/50HZ
Power	2.0kW

### IPX5-6 Water Jet Test Machine introduction:

The water jet test machine adopts the method of spraying water up, down, left, and right to conduct waterproof tests on the equipment, ensuring that the samples can be fully exposed to water spray during the testing process. Moreover, its touch-controlled design allows users to operate through an intuitive graphical interface, set test parameters, and control experimental conditions, making the operation simple and convenient. The left side of the equipment is the control box, and the right side is the water storage tank. The volume of the water tank is about 400L. There is a water level control in the water tank, with a low water level prompt (water shortage alarm).

The sample power socket (220V, 10A) is mounted on the side of the turntable, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding. Equipped with a special water spray bracket, the nozzle can automatically swing up and down and move left and right, so that the water spray covers a wider area. The water spray angle and water spray height can be set through the program.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment. Protection measures: short circuit protection, water shortage alert.

#### Standard technical parameters:

Item	Specification
Diameter of Nozzles	IPX5 : 6.3mm ;
	IPX6 : 12.5mm
Storage tank volume	About 400L
Water flow	IPX5 : 12.5±0.625 L/min ;
	IPX6 : 100.0±5 L/min
Test time	0-999min
Spray distance	2.5-3.0m(controlled by user)
Water spray height	≤1500mm
Horizontal swing angle	±30°
Flow control	Manual adjustment with flow meter
Turntable height	600mm(non-lifting)
Water pressure	Not adjustable (pressure gauge display)
Power supply	380V/50HZ
Power	2.0kW

## Service scene:

Designed for versatility, this equipment caters to waterproof testing needs in electronics, electrical products, automotive systems, motorcycle accessories, and household devices, thereby establishing a strong foundation for product durability, reliability, and uncompromising quality standards.

### Product picture:



spray guns

YUEXIN <sup>®</sup> ~.	uangzhou Yuexin Test Equipment Co., Ltd.
18122303372 mft@yxipx.com raintestchambers.com 101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China	