

# Comprehensive IPX5 Touch Control Water Jet Test Equipment Spray Side and Top

# **Basic Information**

- Place of Origin:
- Brand Name: YueXin

Guangdong, China

usd+20000-50000+pcs

wooden box package

YX-IPX5AS

30-45 days

100+pcs+30

1 pcs

ISO 20653:2013, DIN 40050-9:1993,

IEC60529:2013 VW 80000:2017 LV124 K-10

- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T
- Supply Ability:



# **Product Specification**

• Working Scenarios: Water Spray, Powerful Water Spray Rotating Speed: 0-5 Rounds Per Minute • Turn Table Diameter: 1000mm Controller: 7-inch Touch Screen + PLC • Turntable Height: 600mm (non-lifting) IPX5 • IP Rank: 200KG • Turn Table Load Bearing: • Description: IPX5 IPX6 Water Jet Test Device , Water Jet Environmental Test Machine • Highlight: ipx5 water jet testing machine, ipx6 water jet testing machine,

ipx6 ipx5-6 water jet test machine

Our Product Introduction

# Comprehensive IPX5 Touch Control Water Jet Test Equipment Spray Side and Top

## Generl specifications:

Outline dimension	Approx W 1100×D 900×H 1300 (mm)
Material	304 stainless steel
Power supply	380V/50HZ
Power	2.0kW

## **Description to IPX5 Water Jet Test Machine:**

The spraying method of this equipment is spraying from the side and the top, with a wide coverage, which can make the test results more comprehensive and accurate.

The left side of the equipment is the control box, and the right side is the water storage tank. The volume of the water tank is about 400L. There is a water level control in the water tank, with a low water level prompt (water shortage alarm).

The sample power socket (220V, 10A) is mounted on the side of the turntable, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding. Equipped with a special water spray bracket, the nozzle can automatically swing up and down and move left and right, so that the water spray covers a wider area. The water spray angle and water spray height can be set through the program.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages. Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment. Protection measures: short circuit protection, water shortage alert.

### The main technical parameters:

Item	Specification
Diameter of Nozzles	IPX5 : 6.3mm
Storage tank volume	About 400L
Water flow	IPX5 : 12.5±0.625 L/min
Test time	0-999min
Spray distance	2.5-3.0m(controlled by user)
Water spray height	≤1500mm
Turntable height	600mm(non-lifting)
Flow control	Manual adjustment with flow meter
Horizontal swing angle	±30°
Water pressure	Not adjustable (pressure gauge display)
Power supply	380V/50HZ
Power	2.0kW

#### Service scenario:

The specialized IPX5 and IPX6-compliant rain testing chambers offer a rigorous examination of the waterproof performance of high-end electronic devices, spanning mobile phones, tablets, cameras, and LCD TVs. By replicating the conditions of heavy rain and downpours, they attest to the devices' and their individual components' continued efficacy under extreme weather conditions.

### **Detail photo:**



spray guns

Tags: IPX5 Waterproof Equipment, Water Jet Testing Machine, Water Jet Climatic Machine

