

## 200L High Pressure Water Jet Test Chamber 380V 50HZ With Sensors

Our Product Introduction

for more products please visit us on [raintestchambers.com](http://raintestchambers.com)

### Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10
- Model Number: YX-IPX56KBE-200L
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



### Product Specification

- Product Description: Water Jet Test Chamber
- Controller: 7-inch Touch Screen + PLC
- Viewing Window: Tempered Galss
- Rotating Speed: 1-5 Rounds Per Minute
- IP Grade: IPX5 IPX6
- Usage Scenario: Water Spray / Powerful Water Spray
- Turn Table Diameter: 400mm
- Turn Table Load Bearing: 30KG
- Highlight: **200L Water Jet Test Chamber, High Pressure Water Jet Test Chamber, Water Jet Test Chamber 380V**



## Product Description

### 200L High Pressure Water Jet Test Chamber with Sensors for IPX5 IPX6

#### General specifications:

Dimension	Outline: L1050*W1000*H1600/L2400*W400*H1200; Within: W 600×D 600×H 600 (mm)
Material	External: steel plate Internal: 304 stainless steel
Power supply	380V/50HZ
Power	2.0kW

#### Product information:

This type of water jet test device can withstand the impact of high-pressure water jets. It is usually capable of enduring the rinsing of high-pressure water guns under extreme conditions, ensuring that the equipment can still function normally in harsh environments. Additionally, the flow sensor and pressure sensor equipped within maintains stable measurement performance in complex environments, satisfying monitoring requirements for various occasions.

There is a water storage tank inside the equipment and a water level control system. When the water is full, it will prompt, and when it is short of water, it will alarm.

The sample power socket (220V, 10A) is mounted on the right wall of the inner box, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding<sup>5</sup>.

There is a waterproof lighting inside, which is convenient for users to observe the test situation.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages<sup>6</sup>.

Test time setting: 0-999min<sup>7</sup>.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Protection measures: short circuit protection, water shortage alert.

#### Standard features:

Item	Data
Diameter of Nozzles	IPX5 : 6.3mm; IPX6 : 12.5mm
Water flow	IPX5 : 12.5±0.625 L/min; IPX6 : 100.0±5 L/min
Spray distance <sup>8</sup>	2.7m
Nozzle angle	Fixed, manually adjustable
Turntable height	Approx 100mm (non-lifting)
Power supply	380V/50HZ
Power	2.0kW

#### Remark:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 Standard load-bearing upper limit of turntable is 30kg, but also can be customized per requirements.

5 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

6 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

7 It is recommended to set the test time according to the test standard. The water temperature will rise due to long time test which has an impact on the test results.

8 This distance is the range from the nozzle to the center of the turntable. If the user wants to extend the spraying distance, he needs to explain in advance.

9 The photos may not match the actual ones, and are for user reference only.

#### Product detail images:



water pump                      circuit

**Tags:** Waterproof Test Chamber, IPX5 IPX6 Rain Test Machine, Water Jet Test Chamber



**Guangzhou Yuexin Test Equipment Co., Ltd.**



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China