


IPX56 3375L Pressing Water Jet Testing Equipment By Side Spray With Sensors

Our Product Introduction

for more products please visit us on raintestchambers.com

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013 VW 80000:2017 LV124 K-10
- Model Number: YX-IPX56KBSE-3375L
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Turn Table Load Bearing: 300KG
- Product Title: Rain Test Equipment, Water Jet Test Chamber
- Controller: 7-inch Touch Screen + PLC
- IP Grade: IPX5 IPX6 IPX6K
- Service Scenario: Water Jet、 Powerful Water Spray
- Turn Table Diameter: 1000mm
- Sight Window: Tempered Glass
- Rotating Speed: 1-5 Rounds Per Minute
- Highlight: **Pressing Water Jet Testing Equipment, 3375L Water Jet Testing Equipment**



Product Description

IPX56 3375L Pressing Water Jet Testing Equipment by Side Spray with Sensors

General specifications:

Dimension	Outer: L1950*W1650*H1900/L2400*W400*H1650; Inner: W 1500×D 1500×H 1500 (mm)
Material	External: steel plate; Internal: 304 stainless steel
Power supply	380V/50HZ
Power	2.0kW

Information to IPX5 IPX6 Rain Test Chamber:

This type of rain test chamber is equipped with a floor-mounted side spray technology, which enables it to cover a wider spraying area and achieve a more comprehensive spray effect. Additionally, it can withstand the impact of high-pressure water jets, enduring the flushing from high-pressure water guns under extreme conditions, ensuring the device's normal operation even in harsh environments. Furthermore, it is equipped with flow sensors and pressure sensors that maintain stable measurement performance in complex settings, catering to various flow and pressure monitoring needs across different scenarios.

Two spray modes: up and down sweeping water spray and fixed water spray⁵.

There is a water storage tank inside the equipment and a water level control system. When the water is full, it will prompt, and when it is short of water, it will alarm.

The sample power socket (220V, 10A) is mounted on the right wall of the inner box, which is convenient for the user to do the live test of the sample; and after the sample is powered on, the turntable rotation will be automatically adjusted to forward and reverse rotation to prevent winding⁶.

There is a waterproof lighting inside, which is convenient for users to observe the test situation.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages⁷.

Test time setting: 0-999min⁸.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

Protection measures: short circuit protection, water shortage alert and door open alert⁹.

Standard parameters:

Item	Parameters
Diameter of Nozzles	IPX5 : 6.3mm; IPX6 : 12.5mm
Water flow	IPX5 : 12.5±0.625 L/min; IPX6 : 100.0±5 L/min
Spray distance ¹⁰	2.7m
Spray height ¹¹	1650mm
Nozzle swing speed	0-20 cycle/min
Power supply	380V/50HZ
Power	2.0kW

Announcement:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 Standard load-bearing upper limit of turntable is 50kg, but also can be customized per requirements.

5 If the sample height exceeds 150mm, it is recommended to choose the swing spray method.

6 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

7 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

8 It is recommended to set the test time according to the test standard. The water temperature will rise due to long time test which has an impact on the test results.


9 Door open alert: when the door is open, the test cannot be conducted to protect personnel from being drenched in water.

10 This distance is the range from the nozzle to the center of the turntable. If the user wants to extend the spraying distance, he needs to explain in advance.

11 Since the IPX5 water spray is in a parabolic shape, the water spray range will be lower than this height, and the measured maximum water spray height is close to 700mm.

12 The photos may not match the actual ones, and are for user reference only.

Product photo:



turntable

Tags: Water Jet Testing Machine, IPX5 IPX6 Rain Test Chamber, Water Jet Test Chamber for IPX56

YUEXIN® Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China