

1200L Water Immersion Test Chamber , Sturdy Immersion Test Machine IPX7

Our Product Introduction

for more products please visit us on raintestchambers.com

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO 20653:2013, DIN 40050-9:1993, IEC60529:2013
- Model Number: YX-IPX7B-1200L
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Material: 304 Stainless Steel
- Immersion Depths: ≤ 1.1 Meters
- Water Level Display Mode: Steel Ruler
- Volume: About 1200L
- Observation Window: Toughened Glass
- Operating Scenarios: Immersion Environment
- IP Grade: IPX7
- Commodity Name: Immersion Soaking Test Chamber , IPX7 Waterproof Test Chamber
- Highlight: **1200L Water Immersion Test Chamber , Sturdy Immersion Test Machine, Immersion Test Machine IPX7**



Product Description

1200L Water Immersion Test Chamber, Sturdy Immersion Test Machine for IPX7

General specifications:

Outline size: L1160*W1060*H1300;
Within size: L1000*W1000*H1200

Standard features:

This product is special for its stainless steel outer layer. The front boasts a firm glass window that keeps the tester sturdy while allowing for clear sight inside.

The chassis is made of 304 stainless steel, which is firm and durable. Not only the double-layer structure is adopted but also the inner layer is welded with reinforcing ribs to ensure the reliability of the water tank. There is a stainless steel hook welded on the inside of the box, which is convenient for users to bind ropes and assist in lifting and placing test samples.

The external toughened glass window is convenient for users to observe the test situation. There is a stainless steel ruler attached to the outside of the box, which can visually see the current water level.

Universal casters are mounted on the bottom, which has good load-bearing and easy to move and fix the equipment.

The main technical parameters :

Item	Data
Water depth range	0-1100mm
Water level display mode	Steel ruler, horizontal visual
Steel ruler accuracy	1mm
Window size	Approx W200×H1100mm
Window thickness	12mm
Outer diameter of inlet pipe	Ø 28mm
Water level adjustment method	Manual adjustment valve

Application:

The applicability and significance of the IPX7 water submersion evaluation device extend to a wide range of sectors, such as electronics, electric devices, automotive parts, and beyond. Furthermore, its remarkable capability to withstand substantial water pressures and impacts ensures the safety and dependability of equipment that is required to undergo underwater testing.

Installation requirements:

Aisle: Before the equipment enters the factory, please confirm that the space in the aisle, elevator, laboratory, etc. of the factory area is sufficient for the equipment to pass through.

Water source: Please prepare clean water source(The manufacturer distributes a 6-meter water pipe with an inner diameter of 15mm).

Site space: ≥W900×D1080×2000mm

The laboratory needs to have drains or floor drains and have ventilation conditions.

Notes:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 The water tank only meets the immersion test within 1.1 meters and cannot be pressurized. If the user needs a higher depth test, IPX8 test equipment can be selected.

4 The photos may not match the actual ones, and are for user reference only.

Product detail pictures:



inlet and outlet

Tags: IPX7 Rain Test Chamber, Waterproof Test Chamber, IPX7 Waterproof Immersion Soaking Test Chamber



Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China