

## 1200L IP5X IP6X Environmental Test Chamber , Reliable Sand And Dust Chamber

Our Product Introduction

for more products please visit us on [raintestchambers.com](http://raintestchambers.com)

### Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: IEC60529:2013 , DIN EN 60529-1:2014-09 (VDE 0470-1)
- Model Number: YX-IP56X-1200L
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30




### Product Specification

- Test Function: IP5X IP6X IP5KX IP6KX
- Test Medium: Talcum
- Experimental Scenarios: Dust Environment
- Number Of Dust Outlet: 2
- Material Of Window: Tempered Glass
- Outer Material: Steel Plate
- Sample Rack Load Bearing: 50KG/
- Name: Sand Dust Test Equipment , Dustproof Environmental Chamber
- Highlight: **1200L Environmental Test Chamber , IP6X Environmental Test Chamber , Reliable Sand And Dust Chamber**



### More Images



## Product Description

### 1200L IP5X IP6X Sand Dust Environmental Chamber , Reliable Dust Test Chamber

#### Vacuum system:

The user needs to connect the sample to a special pumping pipe, and the gas inside the sample is pumped out by a vacuum pump, and the pumping speed can be adjusted by an air flow meter.

► Need to reserve the air hole position for the sample.

#### Equipment structure:

Featuring a single, user-friendly door and a meticulously crafted interior, this dust-shielding enclosure successfully keeps out dust from the surroundings, ensuring equipment integrity and making it a fitting solution for tight testing areas.

The talcum powder is blown to the top of the pipeline by the circulation pump and is sprayed out from the dust outlet above the inner box, and moves in disorder after falling freely.

There is a special outlet at the bottom of the funnel, user can quickly collect dust through there.

To keep the test space as dry as possible, a heater is mounted on the outside of the funnel floor.

A vibrator is mounted on the outside of the funnel, which can work intermittently to keep the dust from sticking to the inner wall as much as possible.

The pumping pressure is displayed by the pressure sensor(Unit:kPa), and can be adjusted by the pressure regulating valve;

The pumping speed can be displayed by the flow sensor(Unit:slpm), and the total pumping volume and current pumping speed can be displayed.

The door is transparent and equipped with a window wiper to allow perfect observation of the test space.

The sample power socket (220V, 10A) is mounted under the side of the chassis, which is convenient for the user to do the live test of the sample<sup>6</sup>.

Controller: 7-inch touch screen + PLC, using Yuexin self-developed software, which can be switched to multiple languages<sup>7</sup>.

Casters are mounted to the bottom, and can be adjusted to fix the chassis according to the flatness of the ground.

Protection measures: short circuit protection,blower overload protection.

#### Technical data for IP5X IP6X:

Item	Parameter
Test space volume	1200 L
Number of dust outlet	2
Diameter of the dust outlet	50 mm
Talc Specifications	15 $\mu$ m
Talc dosage	2 4 kg/m <sup>3</sup>
Outer diameter of exhaust pipe	8mm
Pumping speed	Digital display,Unable to adjust
Maximum depression	2kPa(20mbar)
Cycle test times	0-999 times
Test time	0-999 H
Vibration time	0-999 S
Sound pressure level during operation <sup>8</sup>	≤70 dB (measured at 1m in free field)
Power supply	380 V/50 HZ
Sample power <sup>9</sup>	220 V/10 A
Power	3.5 kw

#### Working environment:

Dust-sealed boxes are predominantly utilized as simulators of harsh environments, enabling the examination of products' or equipment's sealing effectiveness and reliability. They are indispensable in sectors like electronics, automotive, and aviation, where they facilitate the testing of electronic devices' dust-proofing abilities, automotive parts' endurance in sandy scenarios, and similar aspects, ultimately ensuring product stability and safety amidst intricate operational conditions.

#### Notes:

1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.

2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.

3 One test only at a time. The next project can be only carried out after the current test is completed. In addition, we can provide multi-functional customized test solutions according to user requirements.

4 A single device is equipped with an exhaust pipe, and only one sample is vacuumed at a time.

5 Please prepare a powder collection box (6-10L) in advance, remove the sealing plate at the bottom of the back, and then collect it.

6 Please inform in advance if the voltage(220V) does not match the actual needs so that we can provide customized solutions for you.

7 At present, only Chinese and English interfaces are supported; if other languages are introduced, the software can be updated remotely.

8 The data is collected in the manufacturer's factory test. It may be different in different environments.

9 If the sample is not suitable for sample testing, a connection hole can be customized on the left side of the inner box, and the user can use an external power supply by himself.

10 The photos may not match the actual ones, and are for user reference only.

The detail photos of product:



inner box

touch screen

**Tags:** Dustproof Climatic Chamber , Dustproof Environmental Chamber , IP5X IP6X Dust Testing Machine



Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China