

304 Stainless Steel Ocean Depth Simulation Test Machine IPX8

Our Product Introduction

for more products please visit us on raintestchambers.com

Basic Information

- Place of Origin: Guangdong , China
- Brand Name: YueXin
- Certification: ISO20653:2013 IEC60529:2013
IEC60598:2021 DIN40050-9:1993
- Model Number: YX-OS100-60L
- Minimum Order Quantity: 1 pcs
- Price: usd+20000-50000+pcs
- Packaging Details: wooden box package
- Delivery Time: 30-45 days
- Payment Terms: T/T
- Supply Ability: 100+pcs+30



Product Specification

- Name: Stainless Steel Ocean Depth Simulation Test Machine
- Material: 304 Stainless Steel
- IP Code: IPX8
- Equipment Weight: About 340KG
- Test Water Depth: 0-100m
- Simulation Environment: Pressurized Water Immersion Environment
- Highlight: **Stainless Steel Ocean Depth Simulation Test Machine**
, Ocean Depth Simulation Test Machine IPX8



More Images



Product Description

100m Deep Ocean Pressure Simulation Tester, Diving Simulation Test Device

Equipment composition:

The ocean depth simulation test chamber is primarily composed of a 304 stainless steel outer casing, a touch screen control system, a pressure controller, safety valves, and other components.

Outer Casing and Tank Body:

Made of 304 stainless steel, they exhibit excellent corrosion resistance and pressure bearing capabilities.

Control System:

Equipped with a touch screen control system, it facilitates users in setting test parameters and monitoring the testing process.

Safety Valves:

These ensure that during the testing process, when the pressure exceeds the set value, it can automatically release the pressure, safeguarding the equipment and personnel's safety.

Product characteristics:

- 1 The Machine is suitable for IPX8 waterproof test or Simulate the deep sea test environment.
- 2 The tank is made of 304 stainless steel material, which can ensure the pressure performance of the container and is not easy to rust.
- 3 All electronic control components are imported from LS, Panasonic, Omron and other brands, and the touch screen adopts a true-color 7-inch screen.
- 4 The pressurization method adopts the water injection pressurization method, the maximum test pressure can be simulated up to 1000 meters, and the equipment is equipped with a safety valve pressure relief valve (mechanical).
- 5 The pressure sensor is used to detect the test pressure and has the effect of stabilizing the pressure; if the pressure in the tank exceeds the pressure, it will automatically open the safety valve to drain water to relieve the pressure.
- 6 The control is equipped with an emergency stop operation button (the pressure is automatically released to 0 meters after pressing the emergency stop).
- 7 Support two test modes, users can choose according to test requirements:
Standard test: The water pressure value and test time can be directly set, and the timing test will start when the water pressure in the tank reaches this value; the alarm will be prompted after the test is over.
Programmable test: 5 groups of test modes can be set. During the test, you only need to select a certain group of modes and press the start button; each group of modes can be divided into 5 continuous test stages, and each stage can be set independently time and pressure values. (In this mode, the number of loop tests can be set)
- 8 Test time setting unit: minute.
- 9 Without a water tank, fill the tank with water after connecting the water pipe, and then pressurize it with a booster pump.
- 10 Casters and foot cups are installed at the bottom of the chassis, which is convenient for users to move and fix.
- 11 Protective device: Leakage switch, pressure safety valve protection, 2 mechanical pressure relief valves, manual pressure relief switch, emergency stop button.

Usage scenario:

Tailored to replicate the pressures of profound ocean depths, this testing machine meticulously examines the waterproof barriers of lamps, home appliances, electronic gadgets, and the like. Upon completion, it validates whether the product shells meet waterproof specifications, guiding manufacturers towards design enhancements and rigorous factory evaluations.

Technical parameter:

Item	Specification
External dimensions	W1070×D750×H1550mm
Inner size	Φ400×H500mm
Wall thickness of the Tank	12mm
Tank material	304 stainless steel material
Flange thickness	40mm
Flange material	304 stainless steel material
Equipment weight	About 340KG
Pressure control mode	Automatic adjustment
Pressure error value	±0.02 Mpa
Pressure display accuracy	0.001Mpa
Test water depth	0-500m
Pressure adjustment range	0-5.0Mpa
Exhaust pressure of the safety valve	5.1Mpa
Test time	0-999 min
Power supply	220V/50HZ
Rated power	100w

Accessories list:

Operating instruction /1pcs

Intake pipe 5 meters

Power Cord /1pcs

Pneumatic wrench /1pcs

Data CD/USB disk /1pcs(May need to be sent separately according to the actual situation)

Notice:

Due to the technical upgrade, some technical parameters do not conform to the actual machine, please forgive us without further notice.

Product detail photos:



jar

jar

Tags: Marine environment simulation test machine, Deep sea pressure simulation test machine, Water pressure environment test equipment



Guangzhou Yuexin Test Equipment Co., Ltd.



18122303372



mft@yxipx.com



raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China