

Guangdong, China

YX-OS200A-100L

usd+20000-50000+pcs

wooden box package

ISO20653:2013 IEC60529:2013 IEC60598:2021 DIN40050-9:1993

YueXin

1 pcs

T/T

30-45 days

100+pcs+30

200m 100L Deep Water Simulation Test Machine For IPX8 Waterproof Testing

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- IP Code:
- Pressure Display:
- Simulation Environment:
- Test Water Depth:
- Equipment Weight:
- Control System:
- Material:

• Highlight:

- Pressure Relief:
- Machine Name:

- IPX8 Pressure Sensor
- Pressurized Water Immersion Environment 0-200m
- About 340KG
- Touch Screen Control
- 304 Stainless Steel
- Safety Valve
- Deep Water Simulation Test Machine

200m Deep Water Simulation Test Machine, 100L Deep Water Simulation Test Machine, IPX8 Deep Water Simulation Test Machine



More Images



200m 100L Deep Water Simulation Test Machine for IPX8 Waterproof Testing

Equipment composition:

The ocean depth simulation test chamber is primarily composed of a 304 stainless steel outer casing, a touch screen control system, a pressure controller, safety valves, and other components.

Outer Casing and Tank Body: Made of 304 stainless steel, they exhibit excellent corrosion resistance and pressure bearing capabilities.


Control System:

Equipped with a touch screen control system, it facilitates users in setting test parameters and monitoring the testing process. Safety Valves:

These ensure that during the testing process, when the pressure exceeds the set value, it can automatically release the pressure, safeguarding the equipment and personnel's safety.

Product details:





exhaust valve

safety valve

Product characteristics:

The deep-sea simulation test machine is a device specifically designed to simulate the high-pressure environment of the deep sea. It features a robust appearance and precise design. Utilizing advanced hydraulic or pneumatic pressure boosting technology, it can highly replicate the high-pressure characteristics of the deep sea, simulating conditions from shallow to deep waters. This equipment precisely controls pressure to test various performance parameters of deep-sea equipment and materials under high pressure.

1 The Machine is suitable for IPX8 waterproof test or Simulate the deep sea test environment.

2 The tank is made of 304 stainless steel material, which can ensure the pressure performance of the container and is not easy to rust.

3 All electronic control components are imported from LS, Panasonic, Omron and other brands, and the touch screen adopts a true-color 7-inch screen.

4 The pressurization method adopts the water injection pressurization method, the maximum test pressure can be simulated up to 1000 meters, and the equipment is equipped with a safety valve pressure relief valve (mechanical).

5 The pressure sensor is used to detect the test pressure and has the effect of stabilizing the pressure; if the pressure in the tank exceeds the pressure, it will automatically open the safety valve to drain water to relieve the pressure.

6 The control is equipped with an emergency stop operation button (the pressure is automatically released to 0 meters after pressing the emergency stop).

7 Support two test modes, users can choose according to test requirements:

Standard test: The water pressure value and test time can be directly set, and the timing test will start when the water pressure in the tank reaches this value; the alarm will be prompted after the test is over.

Programmable test: 5 groups of test modes can be set. During the test, you only need to select a certain group of modes and press the start button; each group of modes can be divided into 5 continuous test stages, and each stage can be set independently time and pressure values. (In this mode, the number of loop tests can be set) 8 Test time setting unit: minute.

9 Without a water tank, fill the tank with water after connecting the water pipe, and then pressurize it with a booster pump.

10 Casters and foot cups are installed at the bottom of the chassis, which is convenient for users to move and fix. 11 Protective device:Leakage switch, pressure safety valve protection, 2 mechanical pressure relief valves, manual pressure relief switch, emergency stop button.

Technical parameter:

Item	Specification
External dimensions	W1100×D750×H1750mm
Inner size	Φ400×H800mm
Wall thickness of the Tank	12mm
Tank material	304 stainless steel material
Flange thickness	40mm
Flange material	304 stainless steel material
Equipment weight	About 340KG
Pressure control mode	Automatic adjustment
Pressure error value	±0.02 Mpa
Pressure display accuracy	0.001Mpa
Test water depth	0-500m
Pressure adjustment range	0-5.0Mpa
Exhaust pressure of the safety valve	5.1Mpa
Test time	0-999 min
Power supply	220V/50HZ
Rated power	100w

Application:

The deep-sea simulation test machine is primarily applied in the fields of scientific research and industrial testing for simulating extreme deepsea environmental conditions. It can recreate the special environments of high pressure, low temperature, and darkness in the laboratory, providing a crucial environmental simulation platform for the development, testing, and validation of deep-sea equipment such as submersibles, underwater sensors, and deep-sea optical cables, ensuring their excellent performance in actual deep-sea applications.

Notice:

Due to the technical upgrade, some technical parameters do not conform to the actual machine, please forgive us without further notice.

Tags: Marine environment simulation test machine , Deep water environment simulation test machine , Water pressure environment test equipment

