IPX8 250L Water Immersion Test Chamber 10m Depth Simulation Yuexin Manufacturer

Basic Information

Place of Origin: Guangdong , China

Brand Name: YueXin

• Certification: ISO 20653:2013, DIN 40050-9:1993,

IEC60529:2013

Model Number: YX-IPX8-10A-250L

Minimum Order Quantity: 1 pcs

Price: usd+20000-50000+pcsPackaging Details: wooden box package

Delivery Time: 30-45 days

Payment Terms: T/T

• Supply Ability: 100+pcs+30



Product Specification

• IP Grade: IPX8

• Test Scenario: Environment Of Long Term Immersion Up To

A Specified Pressure

• Depth Range: 1-10m

Material: 304 Stainless SteelOpening Method: Cylinder Drive

Product Name: Waterproof Immersion Soaking Test

Chamber , Ipx8 Waterproof Test Equipment

• Pressure Accuracy: 1 KPa

• Type: Button Type

• Volume: 250L

• Highlight: Yuexin Water Immersion Test Chamber,

IPX8 Water Immersion Test Chamber, 250L Water Immersion Test Chamber



More Images







Product Description

IPX8 250L Water Immersion Test Chamber 10m Depth Simulation Yuexin Manufacturer

Product introduction:

The IPX8 Immersion Test Equipment is a professional testing device capable of simulating underwater depths up to 10 meters. It features an advanced button-style operation interface, making it convenient for users to easily set test parameters. The equipment is equipped with a cylinder-driven lid, providing exceptional sealing performance to ensure no leakage during testing. The chamber is constructed from high-strength material with a wall thickness of 2mm, ensuring its robustness and durability.

The device is equipped with a pressure sensor, which can display the internal pressure change synchronously.

The tank cover is fastened with stainless steel can lid flange fasteners, and the seal is firm.

Timing is performed by a time relay, and timing starts after the internal pressure reaches the set value.

After the test is complete, the device automatically vents the pressure.

The tank cover is connected with a mechanical safety valve. If the set pressure exceeds the set pressure, the safety valve will release the pressure directly to ensure the safety of users.

The tank lid is lifted and lowered by cylinder driving to reduce operating pressure.

If the user needs to provide an external power supply for the sample, we can open a hole in the lid and provide a locking device (wire diameter <15mm)⁵.

Detail images:





lid

regulating valve

Use scene:

The IPX8 Pressure Immersion Test Machine is primarily intended for replicating underwater depths of varying levels and evaluating the waterproof qualities of product casings. Its versatile testing applications encompass electronics, outdoor lighting, automotive parts, communication gadgets, unmanned aerial vehicles, watches, and more. By utilizing compressed air to elevate water pressure, it simulates authentic underwater conditions to verify the underwater performance of products. This equipment plays a crucial role in various industries in ensuring product reliability.

Generl specifications:

Outer dimension	Approx W 700×D 850×H 1650 (mm)
Pressure accuracy	1 kPa
Power supply	220V/50Hz

Power	100w

The technical data:

Item	Specification
Thickness of lid	15 mm
Flange thickness	20 mm
Tank thickness	3 mm
Equipment net weight	Approx 110 kg
pressure range	0-300 kPa
Water depth(maximum)	10 meters
Adjustment method	Automatic adjustment
Opening method	cylinder drive
Pressure accuracy	1 kPa
pressure error value	±2 kPa
Set pressure of safety valve	0.35 Mpa(350kPa)
Testing time ⁶	0-999 s/min/h
power supply	220V/50Hz
power	100 w

Remark:

- 1 The pictures in this document are for customer reference only, and there may be color differences between the actual model and the pictures.
- 2 This document only lists some test standards, which does not mean that other test requirements and standards cannot be conducted. Welcome to communicate and discuss with us.
- 3 One test only at the same time. The next project can be only carried out after the current test is completed. In addition, we can provide multifunctional customized test solutions according to user requirements.
- $4 \ The formula of the corresponding relationship between pressure and water depth: P=9.8d \ (Unit: kPa,m).$
- 5 Please wear insulating gloves during power-on test to avoid personal safety problems.
- 6 The time unit of the test can be freely selected, and it can be adjusted through the time relay before starting the test.
- 7 The user needs to prepare an air compressor in advance (recommended gas storage capacity > 60L). If you need us to buy it on your behalf, you need to explain in advance.
- 8 The photos may not match the actual ones, and are for user reference only.

About us:









Tags: Water immersion test equipment, IPX8 waterproof test equipment, Environmental testing machine

YUEXIN® Guangzhou Yuexin Test Equipment Co., Ltd.

18122303372

mft@yxipx.com

raintestchambers.com

101, No.3, Jiangjunzi Road, Dalong Street, Panyu District, Guangzhou City China